

# Indoor Ceiling Omni Antenna




**Tone Spread**  
Solutions for Wireless Signal

698-4000 MHz

**CE-698-4000V05i360A**

Specification of 698-3800MHz SISO Low PIM Indoor Ceiling Omni Antenna:

Model	CE-698-4000V05i360A			Product Picture
Frequency Range	698~960	1427~2700	3400~4000	 <div style="border: 1px solid black; padding: 5px; text-align: center; margin: 10px 0;"> <b>698-806/806-960/1427-1710 1710-2700/3400-4000MHz</b> </div> <div style="border: 1px solid black; padding: 5px; text-align: center; margin: 0 auto; width: 100px;"> <b>Port1</b> </div>
Impedance	50Ω			
VSWR	≤1.8	≤1.5	≤1.8	
Gain	2.0dB±0.5	3.0dB±1.0	4.5dB±1.0	
Polarization	Vertical			
Horizontal Beamwidth	360°			
Vertical Beamwidth	70°/90°	35°/40°	30°	
Maximum Power	50W			
Intermodulation	-140dBc@2X43dBm			
Connector Type	N-Female or 4.3/10-Female*			
Lightning Protection	DC Ground			
Dimension	Φ203×115mm			
Radome material	ABS, White Color			
Work Temperature	-40~+55°C			
Weight	0.40kg(0.45kg Packing Weight)			

Antenna Radiation Patterns:

