



698-3800MHz Quadplexer (698-960/1710-2170/2300-2700/3300-3800)

JIETONG DIGITAL

GET CONNECTED

Telecommunication Technology & Engineering Accessories

Rev.V1.0

698-3800MHz Quadplexer (698-960/1710-2170/2300-2700/3300-3800)

PRODUCT CODE	CMB4-0709.1718.1922.2327-4F155S			
Electrical Specifications				
Frequency	690-960MHz	1710-2170MHz	2300-2700MHz	3300-3800MHz
Insertion Loss	≤ 0.4 dB	≤ 0.4 dB	≤ 0.4 dB	≤ 0.4 dB
Isolation	≥50 dB			
Intermodulation	≤ -155 dBc @ 2 x 43 dBm			
VSWR	≤ 1.25			
Impedance	50 Ω			
Power Capacity	≤ 300 W / port			
DC Bypass/Current	Support (≤ 3 A), Customizable for any port			
Environment Specifications				
Lighting Protection	3kA; 10/350 μs pulse			
Safety	EN 60 950			
Environment	ETS 300 019			
Operating Temperature	-35 °C to +65 °C			
Storage Temperature	-40 °C to +85 °C			
Relative humidity	0-95%			
Application	IP67 (Indoor and Outdoor)			
Mechanical Specifications				
Dimensions	195 x 170 x 50 mm			
Weight	≤ 3.0 Kg			
RF Connector	4.3-10 female			
Mounting Type	Wall or Pole			
Installation Brackets	IK-CBAL300, 1 pair (Inclusive)			

Outline Drawing

