
GPS, Galileo, Glonass, Beidou Power Amplifier

Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-10-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	10 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-12-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	12 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-15-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	15 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-20-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	20 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-30-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	30 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	GPS In-line Amplifier	Temperature:	-40°C- +85°C
Model:	GAMP-40-N-F/F	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	40 dB	Annotation:	Indoor Use

V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-10-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 10 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-12-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 12 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-15-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 15 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-20-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 20 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-30-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 30 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS In-line Amplifier Temperature: -40°C- +85°C
Model: GAMP-40-TNC-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: TNC-Female
Gain: 40 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS ADJ Amplifier Temperature: -40°C- +85°C
Model: GPAMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0~30 dB(Adjustable) Annotation: Indoor Use

V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GALILEO ADJ Amplifier Temperature: -40°C- +85°C
Model: GAAMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0~30 dB(Adjustable) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GLONASS ADJ Amplifier Temperature: -40°C- +85°C
Model: GLAMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0~30 dB(Adjustable) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: BEIDOU ADJ Amplifier Temperature: -40°C- +85°C
Model: BDAMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0~30 dB(Adjustable) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GPS Fixed Amplifier Temperature: -40°C- +85°C
Model: GPFMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0/5/10/20/30 dB(Fixed) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GALILEO Fixed Amplifier Temperature: -40°C- +85°C
Model: GAFMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0/5/10/20/30 dB(Fixed) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: GLONASS Fixed Amplifier Temperature: -40°C- +85°C
Model: GLFMP-XX-N-F/F Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0/5/10/20/30 dB(Fixed) Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: BEIDOU Fixed Amplifier Temperature: -40°C- +85°C
Model: BDFMP-XX-N-F/F Impedance: 50 Ω

Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0/5/10/20/30 dB(Fixed)	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS

●GPS,GALILEO,GLONASS,BEIDOU Navigation System Compatibility