

GPS, Galileo, Glonass, Beidou Power Splitter



Item Name:	2 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-2NX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	4 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-4NX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	8 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-8NX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	8 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-8SMAX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	SMA-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	9 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-9NX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	9 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-9SMX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz	Connector:	SMA-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use
V.S.W.R:	≤ 2.00	Waterproof:	IP65 , RoHS



Item Name:	16 Way GPS Splitter	Temperature:	-40°C- +85°C
Model:	PS-GPS-0-16NX	Impedance:	50 Ω
Frequency:	1.1-1.7GHz ●	Connector:	N-Female
Gain:	0 dB±1 dB	Annotation:	Indoor Use

V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: 16 Way GPS Splitter Temperature: -40°C- +85°C
Model: PS-GPS-0-16SMX Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: SM-Female
Gain: 0 dB \pm 1 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: 32 Way GPS Splitter Temperature: -40°C- +85°C
Model: PS-GPS-0-32NX Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: N-Female
Gain: 0 dB \pm 1 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS



Item Name: 32 Way GPS Splitter Temperature: -40°C- +85°C
Model: PS-GPS-0-32SMX Impedance: 50 Ω
Frequency: 1.1-1.7GHz ● Connector: SM-Female
Gain: 0 dB \pm 1 dB Annotation: Indoor Use
V.S.W.R: ≤ 2.00 Waterproof: IP65 , RoHS
