

# UHF DUPLEXER

## JTD-DUP-464-469-50W-N



**JIETONG DIGITAL**

*GET CONNECTED*

*Telecommunication Technology & Engineering Accessories*

Rev.V1.0

### N Type UHF Duplexer (464 /469.675MHz):

Item	JTD-DUP-464-469-50W-N	
Frequency Range ( MHz )	TX: 464.000 MH	RX: 469.675 MHz
Bandwidth(MHz)	12.5 KHz	
VSWR	≤1.35	
Frequency Spacing(MHz)	5.675MHz	
Insertion Loss ( dB )	≤1.5dB	
Isolation ( dB )	≥75dB	
Power (W)	50W	
Impedance ( Ω )	50Ω	
Temperature Range ( °C )	-20~+50℃	
Relative Humidity	0% to 100%	
Connector	N-Female	
Weight(kg)	1.6KG	
Dimensions(mm)	225×190×40(±0.5mm)	

Product Drawing:



Note: The picture is only for reference; please make the object as the standard

*All specifications are subject to change without notice.*

©2021 Jietong Digital Technology Ltd. All Rights Reserved.

Website <http://www.jtd.com.tw>

Add:11169 2F,No 141,Fu-Gang St. Shilin Dist., Taipei City, Taiwan

Tel:+886-2-28828979

Fax:+886-2-28829196

E-Mail: [sales@jtd.com.tw](mailto:sales@jtd.com.tw)